



Wheeled CO2 Extinguisher

HEBA provides Steel bodied **CO2 WHEELED EXTINGUISHERS**, suitable for Fire Class B, and C, ideal for protecting electrical equipments.

The extinguisher body is constructed by special forming process, which is of Seamless Construction. Each cylinder is then subjected to Hydrostatic Pressure at 250 bar (3629 psi).

To give a hard wearing, corrosion resistance as well as gloss finish, each extinguisher is Electro-statically Painted, using a POLYESTER RESIN, before being baked in the oven.



WHEELED
CO2

Other Features of this Range of Extinguishers are:

- Easy to use as one-person can operate.
- Supplied with durable chrome-plated brass valve.
- Supplied complete with safety valve.
- Supplied with durable wire-braid fire hose, and long-lasting black horn, with lance valve as appropriate that can control discharge, this allows optimal use of the fire extinguishing agent.
- Effective discharge without residue.
- Provided with welded tubular-steel frame that protects the cylinder body.
- Assembled complete to tubular-steel frame with high tensile bolts and nuts, this allows both the ability and simplicity when maintaining and re-filling the cylinder.
- Supplied with two special black rubber wheels allow for easy mobility on any surface.



Wheeled CO2 Extinguisher

ITEM PART NO.		CXT10	CXT 25	CXT50
SPECIFICATIONS				
NOMINAL CAPACITY	kg (lb)	10.0 (22.0)	25.0 (55.0)	50.0 (110.0)
EXTINGUISHING AGENT		CO2	CO2	CO2
SHELL MATERIAL		Mild steel	Mild steel	Mild steel
AVERAGE GROSS WEIGHT	kg (lb)	32.50 (71.60)	99.50 (219.20)	194.00 (427.30)
MINIMUM DISCHARGE TIME		Sec	20	20
AVERAGE UNIT HIGHT	mm (in)	1050 (41.34)	1230 (48.43)	1230 (48.43)
SHELL DIAMETER	mm (in)	153 (6.0)	220 (8.6)	500(1) (19.5)
SHELL COLOR		RED	RED	RED
ELECTRICAL NON- CONDUCTIVITY UP TO 1 KV (1000VOLT)		OK	OK	OK
OPERATING TEMPERATURE	UPPER °C	60	60	60
	RANGE °F	140	140	140
	LOWER °C	-20	-20	-20
	RANGE °F	-4	-4	-4

(1) This figure represent wheeled extinguisher width, however shell diameter is as same as 25Kg wheeled one.

Note: All technical specifications changes are reserved
Contact HEBA Fire Fighting Equip. Mfg. or call your local distributor for assistance.

WHEELED
CO2

